



GREENLIGHT SOLUTIONS  
Optical System Design & Supply  
San Bernardo 20-1, 28015 Madrid (Spain)  
Tel: +34 917014880 | Fax: +34 915323132  
info@greenlightsl.com | www.greenlightsl.com

Product Portfolio: Meniscus Lenses  
Author(s) A.Manzanares / L.Perez

Validity: **2009**

### Meniscus Lenses

ID GLS	Focal Length	Diameter	Center Thickness	Edge Thickness	Material	Unit Price (EUR)- 1 unit	Unit Price (EUR) - 5 units	Unit Price (EUR) - 10 units
M15-25-50A	50,00	25,40	5,00	1,30	BK7	113,18	33,46	24,15
M15-25-100A	100,00	25,40	4,00	2,40	BK7	113,18	33,46	24,15
M15-25-150A	150,00	25,40	4,00	2,90	BK7	113,18	33,46	24,15
M15-25-200A	200,00	25,40	3,50	2,70	BK7	113,18	33,46	24,15
M15-25-50B	-50,00	25,40	5,00	9,40	BK7	119,95	40,23	30,92
M15-25-100B	-100,00	25,40	3,00	4,70	BK7	114,53	34,82	25,51
M15-25-150B	-150,00	25,40	3,00	4,10	BK7	114,53	34,82	25,51
M15-25-200B	-200,00	25,40	3,00	3,80	BK7	114,53	34,82	25,51

#### Notes:

All dimensions in millimeters  
Material: BK7 grade A, fine annealed  
Focal Length(f'):  $\pm 2\%$ @587.6nm  
Diameter Tolerance: +0.0/-0.20  
Center Thickness(Tc):  $\pm 0.10$   
Centration: 3'  
Fringes: 1~5  
Irregularity of Fringes: 0.2~0.5  
Surface Quality: 60-40 Scratch-Dig  
Coating: MgF2 AR coated  
Clear Aperture: 90% dia.

#### GENERAL CONDITIONS

VAT	Taxes not included.
Delivery Fees	Not included.
Delivery time	2 weeks
Quotation Validity	2008
Payment form	Pre-payment at the order.