



GREENLIGHT SOLUTIONS  
 Optical System Design & Supply  
 San Bernardo 20-1, 28015 Madrid (Spain)  
 Tel: +34 917014880 | Fax: +34 915323132  
 info@greenlightsl.com | www.greenlightsl.com

Product Portfolio: Fused Silica Plano-Concave Lenses  
 Author(s) A.Manzanares / L.Perez

Validity: 2009

**Fused Silica Plano-Concave Lenses**

ID GLS	Focal Length	Diameter	Center Thickness	Edge Thickness	Material	Unit Price (EUR)- 1 unit	Unit Price (EUR) - 5 units	Unit Price (EUR) - 10 units
SPC19-10-15	-15,00	10,00	2,30	4,50	Fused Silica	118,59	38,88	29,57
SPC19-10-30	-30,00	10,00	2,30	3,20	Fused Silica	118,59	38,88	29,57
SPC19-10-40	-40,00	10,00	2,30	3,00	Fused Silica	118,59	38,88	29,57
SPC19-12-25	-25,40	12,70	3,00	4,90	Fused Silica	121,30	42,89	32,27
SPC19-12-38	-38,10	12,70	3,00	4,20	Fused Silica	121,30	42,89	32,27
SPC19-12-50	-50,80	12,70	3,00	3,90	Fused Silica	121,30	42,89	32,27
SPC19-20-40	-40,00	20,00	3,20	6,10	Fused Silica	122,65	44,24	33,63
SPC19-20-60	-60,00	20,00	3,20	5,10	Fused Silica	122,65	44,24	33,63
SPC19-20-80	-80,00	20,00	3,20	4,60	Fused Silica	122,65	44,24	33,63
SPC19-25-38	-38,10	25,40	3,50	9,00	Fused Silica	126,71	48,31	37,69
SPC19-25-50	-50,80	25,40	3,50	7,30	Fused Silica	126,71	48,31	37,69
SPC19-25-75	-50,80	25,40	3,50	5,90	Fused Silica	126,71	48,31	37,69

**Notes:**

All dimensions in millimeters  
 Material: UV grade fused silica, 200-2500nm  
 Focal Length(f):  $\pm 2\%$ @587.6nm  
 Diameter Tolerance: +0.0/-0.20  
 Center Thickness(Tc):  $\pm 0.10$   
 Centration: 3'  
 Fringes: 1-5  
 Irregularity of Fringes: 0.2~0.5  
 Surface Quality: 60-40 Scratch-Dig  
 Coating: Uncoated  
 Clear Aperture: 90% dia.

**GENERAL CONDITIONS**

VAT	Taxes not included.
Delivery Fees	Not included.
Delivery time	2 weeks
Quotation Validity	2008
Payment form	Pre-payment at the order.

